

Dear All,

Announcing more choices of the Open-Frame Touchmonitors
ELO offers 22", 24" and 27" models.



2440L (24") with PCAP



2740L (27") with IntelliTouch Plus

Product Information:

22" ELO offers 2243L and 2244L with 2243 being the more economical version. Offering iTouch (single touch without bezel), Intellitouch Plus (2 points touch) and Projected Capacitive (2 points touch).

24" ELO offers 2440L which covers iTouch (single touch without bezel), Intellitouch Plus (2 points touch) and Projected Capacitive (*4 points*)

27" ELO offers 2740L Intellitouch Plus (2 points) and the Non touch version available.

Product Specifications:

- * Thin Bezel Style with "Built for Touch" Reliability.
- * Pure-glass touchscreen for optimal image quality.
- * 1080p full HD display with wide viewing angle easily attracts and holds viewer's attention.
- * Multiple mounting options, in both landscape and portrait mode.
- * 22", 24" & 27" diagonal active matrix TFT LED-backlit LCD.
- * 16:9 aspect ratio.
- * Full HD 1920 x 1080 native resolution. Other resolutions supported.
- * All covering with 3 years' warranty.

Designed for touch:

iTouch borderless surface acoustic wave, and IntelliTouch Pro projected capacitive multi-touch technology.

Product Specifications:

Model	2243L	2440L	2740L
Form factor	Open-Frame	Open-Frame	Open-Frame
Color	Brushed Metal	Black	Black
Diagonal size	22 inches (55.88 cm)	24 inches (60.96 cm)	26 inches (66.04 cm)
Aspect ratio	16:9 Widescreen	16:9 Widescreen	16:9 Widescreen
Native (Optimal) Resolution	1920 x 1080	1920x1080	1920 x 1080
Monitor width*	20.1 inches (51.05 cm)	27 inches (68.58 cm)	24.9 inches (63.25 cm)
Monitor height *	11.7 inches (29.72 cm)	17.9 inches (45.47 cm)	14.7 inches (37.34 cm)
Monitor depth*	1.7 inches (4.32 cm)	5.9 inches (14.99 cm)	1.7 inches (4.32 cm)
Brightness (typical, in nits)			
IntelliTouch	225	270	N/A
IntelliTouch Plus	225	270	270
iTouch (No bezel)	N/A	270	N/A
iTouch Plus (No bezel)	N/A	270	N/A
SecureTouch	225	N/A	N/A
Projected Capacitive (No bezel)	225	270	N/A
Viewing angle - total horizontal	170°	170°	178°
Viewing angle - total vertical	160°	160°	178°
Contrast ratio	1000:1	1000:1	3000:1
Response time - total (typical)	5ms	5ms	12ms
Input video format	Analog VGA	Analog VGA and Digital DVI	Analog VGA
Power supply	External DC (Power brick)	External DC (Power brick)	External DC (Power brick)
Input voltage	+12VDC	100-240VAC, 50/60Hz	+12VDC
Power consumption (typical)	22 watts	12 watts	38 watts
Temperature - operating	32°F (0°C) - 104°F (40°C)	32°F (0°C) - 104°F (40°C)	32°F (0°C) - 104°F (40°C)
Temperature - storage	0°F (-18°C) - 140°F (60°C)	-4°F (-20°C) - 104°F (40°C)	-20°F (-29°C) - 60°F (16°C)
Humidity - operating	20% - 80%	20% - 80%	20% - 80%
Humidity - storage	10% - 90%	10% - 90%	10% - 90%
Mean time between failure (MTBF)	50,000 hours	50,000 hours	50,000 hours

Part no. list:

Model	Part No	Technology	Interface	Bezel	Surface Treatment
2243L	E237584	IntelliTouch Plus	USB	Yes	Clear
2243L	E059181	IntelliTouch	USB	Yes	Clear
2243L	E811441	Projected Capacitive	USB	No	Clear
2243L	E378034	SecureTouch	USB	Yes	Clear
2440L	E000413	IntelliTouch	USB/Serial	Yes	Clear
2440L	E000414	iTouch	USB/Serial	No	Clear
2440L	E000415	IntelliTouch Plus	USB	Yes	Clear
2440L	E000416	iTouch Plus	USB	No	Clear
2440L	E000417	Projected capacitive	USB	No	Clear
2740L	E220828	IntelliTouch Plus	USB	Yes	Clear
2740L	E104733	Non touch	N/A	Yes	Clear

For further details on our products, please feel free to contact us
@ +852-2544-0899 or 2543-4921, or via email to sales@touchscreen.com.hk
Marketing Department: Website: <http://www.touchscreen.com.hk>

If you want to unsubscribe to our newsletter, please inform us by a return email!